

SOLAR

design ERIC SOLÉ



- RECESSED LUMINAIRE WITH SOFT LIGHT EMISSION, FOR 1x55W TC-DDEL FLUORESCENT LAMP.
- STEEL BODY WITH WHITE PAINT FINISH.
- INTERNAL REFLECTOR IN METALLIZED THERMOPLASTIC.
- FOR INSTALLATION INTO FALSE CEILING SYSTEMS WITH 600x600MM AND 625x625MM MODULES, SUPPORTED BY THE STRUCTURE ITSELF OR BY MEANS OF AN OPTIONAL SUSPENSION KIT, OR INTO PLASTERBOARD FALSE CEILINGS USING A SPECIAL RECESS FRAME (TO BE ORDERED SEPARATELY).
- ELECTRICAL CONNECTION MADE VIA QUICK CONNECTORS.
- LAMPS CAN BE MAINTAINED WITHOUT THE NEED FOR TOOLS.
- LIGHT OUTPUT RATIO: 54%.
- ELECTRONIC OR DALI-SWITCHDIM DIMMABLE ELECTRONIC BALLAST. OPTIONAL EMERGENCY LIGHTING.
- COMPLIES WITH STANDARD EN60598-1 AND OTHER SPECIFIC STANDARDS.



SOLAR INSTALLATION

		<p>When incorporated into a modular false ceiling structure, SOLAR is installed in the traditional manner.</p>
--	--	--

		<p>When surface mounted, SOLAR is installed by means of a suspension kit (M080403), that holds the fitting in place against the false ceiling.</p>
--	--	--





		<p>SOLAR is equipped with an adjustable bracket system to centre the luminaire, and is suitable for nearly all ceiling types.</p>
--	--	---

		<p>Recessed into plasterboard false ceilings, SOLAR is installed by means of an optional recess frame (M160600/M160602).</p>
--	--	--







ABOVE: FTF-INTERIOR SHOWROOM, MOSCOW (RU).
 PAGE 197: HQ'S MASERATI MODENA (I), STUDIO STURCHIO ARCHITECTS & DESIGNERS.

SOLAR II

				
				
TC-DDELI (GR10q3) 	CODE	LIGHT SOURCE	FALSE CEILING	WEIGHT
	M035500	TC-DDELI (GR10q3) 1x55W non dimmable	600x600mm	5,60kg
	M035507	TC-DDELI (GR10q3) 1x55W non dimmable + emergency 1h	600x600mm	6,20kg
	M035700	TC-DDELI (GR10q3) 1x55W non dimmable	625x625mm	5,70kg

photometric data: see page 427.

SOLAR II DIMMABLE

				
				
TC-DDELI (GR10q3) 	CODE	LIGHT SOURCE	FALSE CEILING	WEIGHT
	M036100	TC-DDELI (GR10q3) 1x55W dimmable DALI	600x600mm	5,60kg
	M033400	TC-DDELI (GR10q3) 1x55W dimmable DALI	625x625mm	5,70kg

photometric data: see page 429.

SOLAR II ACCESSORIES

	M080403 Suspension kit.
	Recess frame for installation into plaster false ceiling. M160600 600x600mm.  606x606mm. 0,90kg. M160602 625x625mm.  633x633mm. 0,94kg.
INTERACTIVE-DALI TECHNOLOGY	INTERACTIVE-DALI components: see page 409.